

Data Sheet For : UD1/G/3666 FINAL

Brand: UD1 / Glazed Panel

SIZE & WEIGHT:

Panel Size : W x D x H_ Imperial Dimensions	36"x2.48"x66"
Panel Size : W x D x H_ Metric Dimension	914x63x1676 MM
Aluminum Color	Powder Coated with RAL7044
Alum Profiles Weight/total weight / Volume (METRIC)	6.2 kg/19.6 kg/0.106 cubic mt
	13.66 lb/43.21 lb/3.75 cubic ft
Fabric Color	Beige Brown Blue Grey

PANEL COMPONENTS & PACKING:

S/N	CODE	Description	QTY	SIZE	TOTAL
S/N	CODE	Intermediate MILL FINISH /17445	5	35"	175"
1	MW0001	Track /26567 (POWDER COATED WITH RAL 7044)	2	1.5"	3"
2	MW0002	Track Cover /17442 (POWDER COATED WITH RAL7044)	2	35"	70"
3	MW0006	Edge /17443 (POWDER COATED WITH RAL 7044)	2	66"	132"
4	MW0009	Top Part /17441 (PWEDER COATED WITH RAL7044)	1	35"	35"
5	MW0010	Aluminum angle for end cap	4	1"	4"
6	MW0051	Glass Part/17444	4 pcs	35"x12"	94"
7	MW0007	MDF (5)MM	2	35"x50"	3500"
8	MW0014	MDF SMALL PART BACK SIDE	6	1.5"x33"	297"
9	MW1001	Clear Float (5mm) Glass	1	34"x11.25"	382.5"
10	MW1002	SPONGE (5)MM	2	39"x54"	4212"
11	MW0050	TOP STEEL SPRING	4	1 1/4X3"	15"
12	MW0059	BOTTOM STEEL SPRING	8	1 1/4	10"
13	MW0060	ADJUSTABLE LEG	2	-	2
14	MW0076	ALUM STRAIGHT	2	2"	4"
15	MW0078	FABRIC	2	39"x54"	4212"
16	MW0110	STABLES 6MM (FABRIC/W/MDF)	520	6 MM	520
18	MW0047	SCREWS 8X1/2"	8	8X1/2"	8
17	MW1003	SCREWS 6X1"	20	6X1"	20
18	MW1004	SCREWS 6X1/2"	24	6X1/2"	24
19	MW1005	STABLES 10MM(MDF/W/MDF)	240	10MM	240
20	MW0052	CORNER CARTOON	4 PCS		
21	MW0077	SHRINK NYLON			

Description:

Short description: Multi-function panel

Long description:

1- Twelve inch (12")Top Glazed Panel.

2- The Alum thickness varies from 1.2 to 3.2 mm depending on the profile code part.

3-The panels are covered with modified upholstery Fabric where it provides diversification of the sound signals (where it is perfect for the call centers and open areas). The fabric is installed on a thin layer of sponge (5mm) for sound absorption.

4- The Glass is clear float glass and it's thickness is 5mm.

5- The bottom part has a track (cable management raceway), for electrical wiring, and punched in 2 locations for the sockets as per the American standard sockets / or the British standard sockets.

6- The side of the shutters has drilled holes to run the cables through.

7-The unit is of a double skin system where fabric can be dismantled from each sides independently and can be replaced, without affecting the other side, all you need to dismantle the fabric part is a spatula.

8- The products are guaranteed for 5 years against manufacturing defect.