

**For : UD1/S/6666 FINAL**  
**Brand: UD1 / Fully Solid Panel**

**SIZE & WEIGHT:**

Panel Size : W x D x H Imperial Dimensions	66"x2.48"x66"
Panel Size : W x D x H Metric Dimension	1676x63x1676 MM
Aluminum Color	Powder Coated with RAL7044
Alum Profiles Weight / Volume	7.15kg/30.3 KG/0.196 CUBIC MT
	15.76 LB/66.8 LB/6.9 CUBIC FT
Fabric Color	Beige   Brown   Blue   Grey

**PANEL COMPONENTS & PACKING:**

S/N	CODE	Description	QTY	SIZE	TOTAL
1	MW0001	Intermediate MILL FINISH /17445	5	65"	325"
2	MW0002	Track /26567 (POWDER COATED WITH RAL 7044)	3	1.5"	4.5"
3	MW0006	Track Cover /17442 (POWDER COATED WITH RAL7044)	2	65"	130"
4	MW0009	Edge /17443 (POWDER COATED WITH RAL 7044)	2	66"	132"
5	MW0010	Top Part /17441 (PWEDER COATED WITH RAL7044)	1	65"	65"
6	MW0051	Aluminum angle for end cap	4	1"	4"
7	MW0014	MDF (5)MM	2	65"X62"	8060"
8	MW1001	MDF SMALL PART BACK SIDE	10	1.5"X63"	945"
9	MW0050	SPONGE (5)MM	2	69"X70"	9660"
10	MW0059	TOP STEEL SPRING	12	1 1/4X3"	45"
11	MW0060	BOTTOM STEEL SPRING	18	1 1/4	22.5"
12	MW0076	ADJUSTABLE LEG	2	-	2
13	MW0078	ALUM STRAIGHT	2	2"	4"
14	MW0110	FABRIC	2	69"X70"	9660"
15	MW0047	STABLES 6MM (FABRIC/W/MDF)	1200	6 mm	1200
16	MW0052	STABLES 10MM (MDF/W/MDF)	640	10MM	640
17	MW1003	SCREWS 8X1/2"	8	8X1/2"	8
18	MW1004	SCREWS 6X1"	20	6X1"	20
19	MW1005	SCREWS 6X1/2"	60	6X1/2"	60
20	MW0077	CORNER CARTOON	4 PCS		
21	MW0048	SHRINK NYLON			

**Description:**

**Short description:** Multi-function panel

**Long description:**

- 1- Full solid panel.
- 2- The Alum thickness varies from 1.2 to 3.2 mm depending on the profile code part.
- 3-The panels are covered with modified upholstery Fabric where it provides diversification of the sound signals (where it is perfect for the call centers and open areas). The fabric is installed on a thin layer of sponge (5mm) for sound absorption.
- 4- The bottom part has a track (cable management raceway), for electrical wiring, and punched in 2 locations for the sockets as per the American standard sockets / or the British standard sockets.
- 5- The side of the shutters has drilled holes to run the cables through.
- 6-The unit is of a double skin system where fabric can be dismantled from each sides independently and can be replaced, without affecting the other side, all you need to dismantle the fabric part is a spatula.
- 7- The products are guaranteed for 5 years against manufacturing defect.