

Data Sheet For : UD2/G/6060 FINAL

Brand: UD2 / Glazed Panel

SIZE & WEIGHT:

Panel Size : W x D x H Imperial Dimensions	
Panel Size : W x D x H Metric Dimension	
Aluminum Color	Powder Coated with WHITE color
Alum Profiles Weight / Volume	kg/3.6
MDF laminated Color	Maple Grey light mahogany

PANEL COMPONENTS & PACKING:

S/N	CODE	Description	QTY	SIZE	TOTAL
1	CW/K4900	TOP PART/SIDE PART SEAL	1	59"	59
2	CW/K4901	TOP POLE	1	59"	59
3	CW/4903	EDGE	2	60"	120
4	CW/K4904	BIG GLASS FRAME	2	59"	118
5	CW/K4905	BIG MIDDLE POLE/INTERMEDIATE	2	59"	118
6	CW/K4906	LITTLE GLASS FRAME	2	12"	24
7	CW/K4907	LITTLE MIDDLE POLE			
8	CW/K4909	2WAY CURVELITTLE MIDDLE POLE/INTERMEDIATED			
9	CW/K4910	T-SHAPE SEAL			
10	CW/K4911	TRAXK COVER/WIRING BOX FOR EASY FIXTURTE	2	59"	118
11	CW/K4139	ALUM PROFILE FPR HOLDIONG ACCESSORIES			
12	MW0001	INTERMEDIATE(7445)	1	59"	59
13	CW/CM3290	2 WAY TOP CAP			
14	CW/CM3291	2 WAY BOTTOM CAP			
15	CW/CM3314	PLASTIC TRACK	3	1.5"	4.5
16	CW/IP25	TABLE HOLDER			
17	CW/TY16	ADJUSTABLE LEG	2		2
18	CW/CM3282	TOP END CAP			
19	CW/CM3283	BOTTOM END CAP			
20	CW/CM3288	TOP JOINT CAP			
21	CW/CM3289	BOTTOM JOINT CAP			
22	CW/CM3292	3 WAY TOP CAP			
23	CW/CM3293	3 WAY BOTTOM CAP			
24	CW/CM3294	4 WAY TOP CAP			
25	CW/CM3295	4 WAY BOTTOM CAP			
26	CW/CM3309	PLASTIC CONNECTOR BETWEEN 2 SHUTTERS			
27	W0019	5 MM MDF LAMINATED	2	59"x49"	5782
28	MW1002	5MM GLASS	1	59"x11.25"	663.75
29	MW1001	Small MDF 18 mm for fixing the 5mm MDF	5	55"x1"	275
30	MW1004	SCREWS 6X1"	12	6X1"	12
31	MW0077	CORNER CARTOON FOR 3CM	4	3CM	4
32	MW0048	SHRINK NYLON			

Description:

Short description: Multi-function panel

Long description:

- 1- Full solid panel.
- 2- The Alum thickness varies from 1.0 to 1.2 mm depending on the profile code part.
- 3-The panels are covered with modified upholstery Fabric where it provides diversification of the sound signals (where it is perfect for the call centers and open areas). The 5MM MDF is laminated with wood grain shapes / fabric can be installed instead of the laminated MDF.
- 4- The bottom part has a track (cable management raceway), for electrical wiring, and punched in 2 locations for the sockets as per the American standard sockets / or the British standard sockets.
- 5-The unit is of a double skin system where fabric can be dismantled from each sides independently and can be replaced, without affecting the other side, all you need to dismantle the fabric part is a spatula.
- 6- The products are guaranteed for 3 years against manufacturing defect.