Data Sheet For: UD2/S/2466 FINAL

**Brand: UD2 / Solid Panel** 

## **SIZE & WEIGHT:**

Panel Size: W x D x H Imperial Dimensions			
Panel Size: W x D x H Metric Dimension			
Aluminum Color Powder Coated with WHITE or			
Alum Profiles Weight / Volume	kg/1.45		
MDF laminated Color	Maple   Grey   light mahogany		

## **PANEL COMPONENTS & PACKING:**

S/N	CODE	Description	QTY	SIZE	TOTAL
1	CW/K4900	TOP PART/SIDE PART SEAL	1	23"	23
2	CW/K4901	TOP POLE	1	23"	23
3	CW/4903	EDGE	2	66"	132
4	CW/K4905	BIG MIDDLE POLE/INTERMEDIATE	1	23"	23
5	CW/K4911	TRAXK COVER/WIRING BOX FOR EASY FIXTURTE	2	23"	46
6	MW0001	INTERMEDIATE(7445)	1	23"	23
7	CW/CM3314	PLASTIC TRACK	2	1.5"	3
8	CW/TY16	ADJUSTABLE LEG	2		2
9	W0012	5 MM MDF LAMINATED	2	23"X61"	2806
10	MW1001	Small MDF 18 mm for fixing the 5mm MDF	5	18"X1"	108
11	MW1004	SCREWS 6X1"	10	6X1"	10
12	MW0077	CORNER CARTOON FOR 3CM	4	3CM	4
13	MW0048	SHRINK NYLON			

## **Description:**

**Short description:** Multi-function panel

## **Long description:**

- 1- Full solid panel.
- 2- The Alum thickness varies from 1.0 to 1.2 mm depending on the profile code part.
- 3-The panels are covered with modified upholstery Fabric where it provides diversification of the sound signals (where it is perfect for the call centers and open areas). The 5MM MDF is laminated with wood grain shapes / fabric can be installed instead of the laminated MDF.
- 4- The bottom part has a track (cable management raceway), for electrical wiring, and punched in 2 locations for the sockets as per the American standard sockets / or the British standard sockets.
- 5-The unit is of a double skin system where fabric can be dismantled from each sides independently and can be replaced, without affecting the other side, all you need to dismantle the fabric part is a spatula.
- 6- The products are guaranteed for 3 years against manufacturing defect.